



Parts Included - Two (2) *FasTrak™* mounting brackets, (4) strips adhesive hook-tape (2-long/2-short), (4) snap screws

Required Tools – ¼" ratchet, 7mm or 5/16 socket, T-15 torx bit, scissors, stubby Phillips screwdriver

Required Cleaning Supplies – wax/polish, vinyl dressing, clean rags

Pre Installation

- 1) Carefully read and follow instructions to ensure optimal performance (**for C6-Z06, Note Steps #10 & 11**).
- 2) Thoroughly wash & wax vehicle surfaces including inside wheel wells and under front bumper, to prevent entrapment of moisture and/or debris between paint finish and *SpeedLingerie™*.
- 3) Place unfolded *SpeedLingerie™* in direct sunlight, or near (but not in direct contact with) any radiant heat source for 20-30 minutes to warm-up the *SpeedLingerie™*. Park the car in direct sunlight to warm-up the front-end surface.
NOTE! Warming the *SpeedLingerie™* and the vehicle front-end will make the *SpeedLingerie™* more flexible and easier to install.
- 4) Orient yourself with *SpeedLingerie™*. Notice placement correlation of mesh and grills.
- 5) For easier access to wheel well area, turn the steering wheel to the passenger side.

FasTrak™ Bracket Installation

- 1) Start on the driver side.
- 2) **Note:** There are (5) T-15 Torx screws that hold the wheel well liner to the fender. Remove all (5) screws.
- 3) Orient the *FasTrak™* bracket with the straight-edge outward, the bumps for the screw holes inward, and the flat side contacting the wheel well liner.
- 4) Align the *FasTrak™* bracket with the wheel well surface and screw holes.
- 5) Re-install each screw.
- 6) At the passenger side repeat steps #2-4 on the driver side.

Top Edge Hook-Tape Installation

- 1) Open the hood.
- 2) **Note:** With the hood in the "up" position, there are (4) screws just inside the top edge of the nose.
- 3) Use the 7mm or 5/16" socket and ratchet to removed all (4) screws.
- 4) Install the adhesive backed hook-tape to the surface where the screws are located.
- 5) Re-install and securely fasten the screws.

Brake Duct Hook-Tape Installation

- 1) Start at the driver side brake duct.
- 2) **Note:** There are (2) factory screws just inside the edge of the spoiler at the brake duct.
- 3) Use the 7mm or 5/16" socket and ratchet to remove both screws.
- 4) Test-fit the hook-tape first. Align and install the adhesive backed hook-tape to the surface where the screws are located.
- 5) Replace the (2) factory screws, with (2) snap- screws, and tighten them.
- 6) At the passenger side brake duct, repeat steps #1-5.

SpeedLingerie Nose Cover Installation

- 1) Open the hood.
- 2) Face the front of the vehicle. Hold the properly oriented *SpeedLingerie™* outstretched in front of you.
- 3) Attach the top edge of the Nose Cover to the hook-tape you installed in "Top Edge Hook-Tape Installation", so the *SpeedLingerie™* hangs in place (align the top edge holes with the screw heads to confirm left to right position).
- 4) At the passenger side, note the long/main section of *QuiKlip™* side fastener (do not yet attach the side small top clip). Start at the top. Flip the *QuiKlip™* fastener into the *FasTrak™* bracket and work your way down.
- 5) **NOTE!** Due to the perfectly tailored fit of *SpeedLingerie™*, step#6 takes careful effort. Acquire assistance, to provide "slack" from the front-end midpoint. **DO NOT** pull on the molded fastener/stitching itself. **DO NOT** pull from the top edge. Installation becomes easier with repeated use.
- 6) Working from the passenger side, come across the front end and carefully but firmly stretch the *SpeedLingerie™* towards the driver side. Gather 6-8" of material at the molded fastener strip in your hands, and carefully but firmly pull from the side at the midpoint and the lower corner (spoiler level). Repeat step#4 to clip the fastener on the driver side.

(Corvette C6Z06 – continued)

- 7) At the driver side, attach the small side top clip to the edge of the wheel well.
- 8) Repeat step#7 on the passenger side.
- 9) Loosen the Velcro at the top edge of the *SpeedLingerie™*.
- 10) **Note: !VERY IMPORTANT!** On the vehicle, at the spoiler, there is a gap between the body and the spoiler. Inside the *SpeedLingerie™*, at the spoiler, there is a tongue/tab sewn to the inside bottom edge of the Nose Cover.
- 11) Insert the tongue/tab on the inside of the Nose Cover, into the gap between the body and the spoiler. This secures the bottom edge of the *SpeedLingerie™* to the vehicle (otherwise the bottom edge will 'ride up').
- 12) Attach the (4) snaps through the brake intake ducts where there are snaps.
- 13) Attach the (2) *QuiKlips™* into the remaining brake ducts.
- 14) Attach the (2) *QuiKlips™* bottom side edges to the bottom side edge of the spoiler (just in front of the wheel wells).
- 15) Flip the Flat Tabs at the top edge of the *SpeedLingerie™* into the gaps just inside each headlight assy.

Mirror Cover Installation

- 1) To differentiate between passenger and driver side mirror cover, the vinyl covered loop portion of the hook & loop fastener folds down and over the hooked portion.
- 2) Lower/open windows. Close doors. Enjoy the opportunity to work with your car and take your time.
- 3) Begin at passenger side. Open the hook & loop tab.
- 4) Stretch out mirror cover tension cord and slip the cover over the mirror head. **NOTE!** Support the mirror head properly during installation.
- 5) Form the mirror cover into place using both hands and temporarily fasten the hook and loop tab. NOTE! Refer to Pre-installation Step #1 if you are unsure whether you are installing the appropriate mirror cover on the correct side.
- 6) With both hands, continue forming the mirror cover into place (like molding clay). Adjust material around face of mirror until mirror-opening edges at tension cord align and meet. You may need to open/close hook & loop tab several times during this process.
- 7) Repeat Steps # 2 – 5 at driver side.

Final Adjustment

- 1) Adjust *SpeedLingerie™* where necessary, to assure proper fit.
- 2) For full effect of *SpeedLingerie™* design and glove-like fit, allow 72 hours for material(s) to relax and conform to vehicle's curves.
- 3) Park in a warm sunny spot with *SpeedLingerie™* on for a few days, to help the process.
- 4) You may apply a quality vinyl conditioner if you so desire.

Care & Maintenance

- 1) For best results, be sure that vehicle surfaces are clean and dry before installing *SpeedLingerie*.
- 2) Always inspect *SpeedLingerie™* fasteners and surfaces that contact vehicle for possible debris, sand, grit, etc... and remove before installation.
- 3) Periodically remove *SpeedLingerie™* to allow complete aeration of vehicle paint finish and *SpeedLingerie* materials.
- 4) Remove *SpeedLingerie™* before washing vehicle.
- 5) Remove *SpeedLingerie™* after exposure to rain or other fluids/moisture.
- 6) Clean outer vinyl surfaces of *SpeedLingerie™* with a high quality conditioner during routine car maintenance.
- 7) Clean felt inner surface with water if necessary, allowing it to dry completely, and brush/vacuum out any remaining particles.
- 8) Rubber will stain vinyl. **DO NOT** store your *SpeedLingerie™* in direct contact with rubber products (ie: tires, hoses, etc) as vinyl is a very porous material and will absorb the black carbon in rubber products, resulting in a stain on the vinyl.

Congratulations again on the purchase of your *SpeedLingerie™*.

For installation questions call 1(800) 570-1579 or email support@speedlingerie.com